


Data Sheet

PRODUCT: **EVOHFLEX PRO BLACK PIPE 5 LAYERS PEX-B**

Our ref: **PSRTPEX01**



Picture of the product



Description

- EVOHFLEX PRO BLACK Anti-diffusion Pex-b pipe
- Certified according to UNE EN ISO 15.875
- It incorporates external polymer coating with metallic microparticles to prevent moisture from coming into contact with the Evoh layer:
 - Reduces oxygen absorption
 - Reduces corrosion
 - Increases thermal performance
 - Protects against abrasion during construction
 - Facilitates installation

Characteristics of the product



Mechanical characteristics

Roughness value	0,007 mm
Thermal conductivity	0,37 W/K*m
Linear coefficient of expansion	0,15 mm/m*K
Working temperature range	From -20°C up to +90°C
Radius of curvature	6*D
Tensile strength	20 N/mm ² (DIN53455)
Elongation at break	400% (DIN53455)
Module E	557 Mpa (DIN53457)
Working field according to UNE EN 22391	Serie 4 Class 5 PN20
Field of application	Air conditioning and heating installations.
Pipe diameters	Ø15, Ø16, Ø18, Ø20, Ø25 and Ø32

Product certified according to Aenor

Certificate no.: 001/0006331